

MATERIAL SAFETY DATA SHEET

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATHESON TRI-GAS, INC.
959 ROUTE 46 EAST
PARSIPPANY, NEW JERSEY 07054-0624

EMERGENCY CONTACT:
CHEMTREC 1-800-424-9300
INFORMATION CONTACT:
973-257-1100

SUBSTANCE: SILANE

TRADE NAMES/SYNONYMS:

MTG MSDS 78; MONOSILANE (SIH4); SILICANE; SILICON HYDRIDE (SIH4); SILICON TETRAHYDRIDE; SILICON HYDRIDE; MONOSILANE; STCC 4920168; UN 2203; H4Si; MAT20590; RTECS VV1400000

CHEMICAL FAMILY: hydrides

CREATION DATE: Jan 24 1989

REVISION DATE: Dec 16 2002

SECTION 2 COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENT: SILANE
CAS NUMBER: 7803-62-5
PERCENTAGE: 100.0

SECTION 3 HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH=2 FIRE=4 REACTIVITY=3



EMERGENCY OVERVIEW:

COLOR: colorless

PHYSICAL FORM: gas

ODOR: unpleasant odor

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation

PHYSICAL HAZARDS: May explode on contact with water. Flammable gas. May cause flash fire. Extremely flammable. May ignite spontaneously on exposure to air.

POTENTIAL HEALTH EFFECTS:

INHALATION:

SHORT TERM EXPOSURE: irritation, nausea, headache

LONG TERM EXPOSURE: no information is available

SKIN CONTACT:

SHORT TERM EXPOSURE: irritation, blisters

LONG TERM EXPOSURE: same as effects reported in short term exposure

EYE CONTACT:**SHORT TERM EXPOSURE:** irritation, blurred vision**LONG TERM EXPOSURE:** same as effects reported in short term exposure**INGESTION:****SHORT TERM EXPOSURE:** frostbite**LONG TERM EXPOSURE:** no information is available

SECTION 4 FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.**SKIN CONTACT:** Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.**EYE CONTACT:** Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.**INGESTION:** If a large amount is swallowed, get medical attention.

SECTION 5 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Severe fire hazard. May ignite on exposure to air. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back.**EXTINGUISHING MEDIA:** carbon dioxide, regular dry chemical

Large fires: Use regular foam or flood with fine water spray.

FIRE FIGHTING: Move container from fire area if it can be done without risk. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire. Evacuation radius: 500 meters (1/3 mile). Consider downwind evacuation if material is leaking.**LOWER FLAMMABLE LIMIT:** 1%**UPPER FLAMMABLE LIMIT:** 100%

SECTION 6 ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE:

Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering.

SECTION 7 HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances. Store above -110 C. Store in a tightly closed container. May ignite on exposure to air.

SECTION 8 EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:**SILANE:**

5 ppm (7 mg/m³) OSHA TWA (vacated by 58 FR 35338, June 30, 1993)

5 ppm ACGIH TWA

5 ppm (7 mg/m³) NIOSH recommended TWA 10 hour(s)

VENTILATION: Provide local exhaust ventilation system. Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Wear helmet with full face shield and fire-proof hood to prevent any possibility of burns if in contact with this substance.

CLOTHING: Wear appropriate chemical resistant clothing.

GLOVES: Wear fire-resistant gloves.

RESPIRATOR: Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.

Any self-contained breathing apparatus with a full facepiece.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: gas

COLOR: colorless

ODOR: unpleasant odor

MOLECULAR WEIGHT: 32.12

MOLECULAR FORMULA: Si-H4
BOILING POINT: -170 F (-112 C)
FREEZING POINT: -301 F (-185 C)
VAPOR PRESSURE: Not available
VAPOR DENSITY (air=1): 1.3
SPECIFIC GRAVITY: Not applicable
DENSITY: 1.342 g/L @ 20 C
WATER SOLUBILITY: insoluble
PH: Not applicable
VOLATILITY: 100%
ODOR THRESHOLD: Not available
EVAPORATION RATE: Not applicable
VISCOSITY: 0.01092 cP @ 25 C
COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable
SOLVENT SOLUBILITY:
Insoluble: ethanol, benzene, ether, chloroform, silicochloroform, silicon tetrachloride

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: May ignite on exposure to air.

CONDITIONS TO AVOID: Avoid heat, flames, sparks and other sources of ignition. Containers may rupture or explode if exposed to heat.

INCOMPATIBILITIES: metal salts, bases, halogens, oxidizing materials

HAZARDOUS DECOMPOSITION:
Thermal decomposition products: silicon, hydrogen

POLYMERIZATION: Will not polymerize.

SECTION 11 TOXICOLOGICAL INFORMATION

SILANE:

TOXICITY DATA:
9600 ppm/4 hour(s) inhalation-rat LC50

LOCAL EFFECTS:
Irritant: inhalation, skin, eye

ACUTE TOXICITY LEVEL:
Slightly Toxic: inhalation

MUTAGENIC DATA: Available.

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATIONS

Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. Dispose in accordance with all applicable regulations.

SECTION 14 TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:
PROPER SHIPPING NAME: Silane, compressed
ID NUMBER: UN2203
HAZARD CLASS OR DIVISION: 2.1
LABELING REQUIREMENTS: 2.1



CANADIAN TRANSPORTATION OF DANGEROUS GOODS:
SHIPPING NAME: Silane, compressed
ID NUMBER: UN2203
CLASSIFICATION: 2.1

SECTION 15 REGULATORY INFORMATION

U.S. REGULATIONS:
CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4): Not regulated.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30): Not regulated.

SARA TITLE III SECTION 304 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.40): Not regulated.

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):
ACUTE: Yes
CHRONIC: No
FIRE: Yes
REACTIVE: Yes
SUDDEN RELEASE: Yes

SARA TITLE III SECTION 313 (40 CFR 372.65): Not regulated.

OSHA PROCESS SAFETY (29CFR1910.119): Not regulated.

STATE REGULATIONS:
California Proposition 65: Not regulated.

CANADIAN REGULATIONS:
WHMIS CLASSIFICATION: AB

NATIONAL INVENTORY STATUS:
U.S. INVENTORY (TSCA): Listed on inventory.

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CANADA INVENTORY (DSL/NDSL): Not determined.

SECTION 16 OTHER INFORMATION

MSDS SUMMARY OF CHANGES

SECTION 15 REGULATORY INFORMATION

©Copyright 1984-2002 MDL Information Systems, Inc. All rights reserved.

MATHESON TRI-GAS, INC. MAKES NO EXPRESS OR IMPLIED WARRANTIES, GUARANTEES OR REPRESENTATIONS REGARDING THE PRODUCT OR THE INFORMATION HEREIN, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR USE. MATHESON TRI-GAS, INC. SHALL NOT BE LIABLE FOR ANY PERSONAL INJURY, PROPERTY OR OTHER DAMAGES OF ANY NATURE, WHETHER COMPENSATORY, CONSEQUENTIAL, EXEMPLARY, OR OTHERWISE, RESULTING FROM ANY PUBLICATION, USE OR RELIANCE UPON THE INFORMATION HEREIN.